







## TRUETYPE COLLECTIONS

TrueType Collections (.ttc files) contain more than one font. mPDF treats each font separately by defining the TTCfontID array in the config\_fonts.php configuration file.

This example uses the Windows MingLiU fonts, which consist of 2 files containing 6 fonts (note that mingliub is not a Bold variant):

Font collection file (mingliu.ttc) contains the following fonts:

- [1] MingLiU (mingliu) Regular
- [2] PMingLiU (pmingliu) Regular (Proportional)
- [3] MingLiU\_HKSCS (mingliu\_hkscs) Regular

Font collection file (mingliub.ttc) contains the following fonts:

- [1] MingLiU-ExtB (mingliu-extb) Regular
- [2] PMingLiU-ExtB (pmingliu-extb) Regular (Proportional)
- [3] MingLiU\_HKSCS-ExtB (mingliu\_hkscs-extb) Regular

This is a sample entry in the config\_fonts.php configuration file:

```
$this->fontdata = array(
    "mingliu" => array(
        'R' => "mingliu.ttc",
        'TTCfontID' => array (
            'R' => 1,
        ),
        'sip-ext' => 'mingliu-extb',
    ),
    "pmingliu" => array(
        'R' => "mingliu.ttc",
        'TTCfontID' => array (
            'R' => 2,
        ),
        'sip-ext' => 'pmingliu-extb',
    ),
    "mingliu_hkscs" => array(
        'R' => "mingliu.ttc",
        'TTCfontID' => array (
            'R' => 3,
        ),
        'sip-ext' => 'mingliu_hkscs-extb',
    ),
    "mingliu-extb" => array(
        'R' => "mingliub.ttc",
        'TTCfontID' => array (
            'R' => 1,
        ),
    ),
    "pmingliu-extb" => array(
        'R' => "mingliub.ttc",
        'TTCfontID' => array (
            'R' => 2,
        ),
    ),
    "mingliu_hkscs-extb" => array(
        'R' => "mingliub.ttc",
        'TTCfontID' => array (
            'R' => 3,
        ),
    ),
);
```

This is sample HTML code:

```
<div style="font-family:mingliu;"> &#40706; &#40742; &#40772; &#40784; &#40802; &#40809;  
&#x23289; &#x2328a; </div>  
<div style="font-family:mingliu_hkscs;"> &#40706; &#40742; &#40772; &#40784; &#40802; &#40809;  
&#x23289; &#x2328a; </div>  
<div style="font-family:pmingliu;"> &#40706; &#40742; &#40772; &#40784; &#40802; &#40809;  
&#x23289; &#x2328a; </div>
```